

# Front Coil-Over Conversions for GM A-Arms

Converting your stock GM A-arm front suspension to coil-over shocks is now a simple bolt-on procedure. Our exclusive ball-stud upper-mount assembly bolts to the factory upper-shock-stem mount, replacing compliant rubber bushings with spherical-bearing precision. The urethane-bushed lower crossbar mounts directly to the factory or aftermarket lower A-arm. Lightweight billet-aluminum VariShock coil-overs are available in 16-position single-adjustable or 256-combination double-adjustable versions. Four travel lengths are available; 3.5" for OEM-positioned shock mounts on stock or aftermarket arms, 4.25" for aftermarket arms with lowered shock mounts, and 2.8" and 5.15" versions available special order. To eliminate side-load forces and extend internal seal service life non-conical, 2-1/2"-ID VariSprings are used. A cylindrical shaped spring reduces weight and allows a larger selection of springs rates. Choice of spring rates range from 450 to 850 lb/in, suitable for street-friendly ride quality to

larger-vehicle handling performance. A second set of different rate springs can also be selected as an option for tuning purposes. Kits include shocks, springs, mounting hardware, and spanner wrench. All shock components and hardware are plated, anodized, or powder coated for a long-lasting quality appearance. Shocks and springs are packaged in pairs.

*Fits various GM applications with lower A-arm mounted shock*

VariShock GM Coil-Overs



1/2" poly eye for use with aftermarket A-arm

Crossbar for use with factory A-arm

Coil-over kit includes springs, upper ball-stud mount, urethane-bushed lower crossbar or eye-style mount, upper spring seat, threaded locking lower spring collar, and spanner wrench.

PART NUMBER	VALVING	LOWER MOUNT	TOTAL TRAVEL <sup>1</sup>	COLLAPSED LENGTH	EXTENDED LENGTH	RIDE-HEIGHT MINIMUM	RIDE-HEIGHT MAXIMUM	SPRING LENGTH	PRICE <sup>2</sup> EACH
VAS 861MN-350	SINGLE	CROSSBAR <sup>3</sup>	3.50"	9.63"	13.13"	11.03"	11.73"	7"	\$334.00
VAS 861MN-425	SINGLE	CROSSBAR <sup>3</sup>	4.25"	10.38"	14.63"	12.08"	12.93"	9"	334.00
VAS 861MQ-350	SINGLE	1/2 EYE <sup>4</sup>	3.50"	9.63"	13.13"	11.03"	11.73"	7"	324.00
VAS 861MQ-425	SINGLE	1/2 EYE <sup>4</sup>	4.25"	10.38"	14.63"	12.08"	12.93"	9"	324.00
VAS 862MN-350	DOUBLE	CROSSBAR <sup>3</sup>	3.50"	9.63"	13.13"	11.03"	11.73"	7"	434.00
VAS 862MN-425	DOUBLE	CROSSBAR <sup>3</sup>	4.25"	10.38"	14.63"	12.08"	12.93"	9"	434.00
VAS 862MQ-350	DOUBLE	1/2 EYE <sup>4</sup>	3.50"	9.63"	13.13"	11.03"	11.73"	7"	424.00
VAS 862MQ-425	DOUBLE	1/2 EYE <sup>4</sup>	4.25"	10.38"	14.63"	12.08"	12.93"	9"	424.00

OPTION SECOND SET OF DIFFERENT RATE SPRINGS FOR TUNING 100.00

NOTES 1 - 2.80" AND 5.15" TRAVEL LENGTHS ARE AVAILABLE SPECIAL ORDER

2 - SOLD IN PAIRS UNLESS OTHERWISE NOTED

3 - CROSSBAR IS FOR USE OEM-STYLE CONTROL ARM MOUNT

4 - 1/2"-EYE IS FOR USE WITH AFTERMARKET CONTROL ARM CLEVIS MOUNT